



100 SERIES

UNIVERSAL AQUA

- Sealed recessed downlight with deep set reflector
- IP54 to ceiling for wet room applications
- Die-cast construction
- Glare control secondary reflector
- Supplied with pre-wired remote non-dimming driver

500/700/1000/1300lm CRI 80+
500/700/1000/1300lm CRI 98

2000/3000lm CRI 80+
2000lm CRI 98



Cut Out: Ø95mm



Accessories

To order, use the following suffix



Nickel Satin option

PRODUCT CODE

Lumen Output:

- (05) 500 lm
- (07) 700 lm
- (10) 1000 lm
- (13) 1300 lm
- (20) 2000 lm
- (30) 3000 lm

Colour Temps:

- (27) 2700K
- (30) 3000K
- (35) 3500K
- (40) 4000K

(3500K available in 700 Lumens and above)

Colour Rendering:

- (V8) Vibrancy 80
- (V9) Vibrancy 98
- (80) CRI 80+
- (98) CRI 98

(CRI98 / V9 up to 2000 Lumens)

Beam Angles:

- (M) Medium: 40°
- (W) Wide: 60°

Colour:

- (W) White
- (B) Black
- (N) Nickel Satin

AQ

/**/**

Options:

Dimming:

- /DT Trailing Edge
- /DL Leading Edge
- /DD DALI
- /DA Analogue (1-10V)
- /LT Lumentalk

Options:

- /M3 3Hrs Maintained
- /ST Self Test
- /DE DALI Emergency

(Other dimming options available see page 123)

